

AMENDMENTS TO THE CLAIMS

1-8. (Canceled)

9. (Currently amended) A resist composition comprising a resin component (A) that undergoes a change in alkali solubility in the presence of acid, and an acid generator component (B) that generates acid on exposure, wherein:

said resin component (A) has a weight average molecular weight of no more than 7,500 and comprises structural units (a) derived from a (meth)acrylate ester,



wherein said structural units (a) comprise structural units (a1) derived from a (meth)acrylate ester containing an acid dissociable, dissolution inhibiting group,

structural units (a2) derived from a (meth)acrylate ester comprising a lactone-containing monocyclic or polycyclic group, and

structural units (a3) derived from a (meth)acrylate ester comprising a hydroxyl group-containing aliphatic hydrocarbon group; and wherein

said component (B) comprises at least one ~~a~~ sulfonium compound represented by a general formula (b-1) or a general formula (b-2) shown below:

[Formula 1]



[wherein, X represents an alkylene ~~a perfluoroalkylene group of 2 to 6~~ 3 carbon atoms in which at least one hydrogen atom has been substituted with a fluorine atom; Y and Z each represents, independently, an alkyl group of 1 to 10 carbon atoms in which at least one hydrogen atom has

been substituted with a fluorine atom; R¹ to R³ each represents, independently, an aryl group or an alkyl group, and at least one of R¹ to R³ represents an aryl group].

10. (**Previously presented**) A resist composition according to claim 9, wherein said component (B) further comprises an onium salt-based acid generator comprising a straight-chain fluorinated alkylsulfonate anion of 1 to 7 carbon atoms.

11. (**Previously presented**) A resist composition according to claim 9, further comprising a nitrogen-containing organic compound.



12. (**Previously presented**) A method for forming a resist pattern, comprising the steps of forming a resist film on a substrate using a resist composition according to claim 9; conducting selective exposure treatment of said resist film; and alkali developing said resist film to form said resist pattern.

13. (**Previously presented**) A resist composition, comprising a resin component (A) that undergoes a change in alkali solubility in the presence of acid, and an acid generator component (B) that generates acid on exposure, wherein

said resin component (A) has a weight average molecular weight of no more than 8,000 and comprises structural units (a) derived from a (meth)acrylate ester;

said component (B) comprises at least one sulfonium compound represented by a general formula (b-1) or a general formula (b-2) shown below:

[Formula 1]



[wherein, X represents an alkylene group of 2 to 6 carbon atoms in which at least one hydrogen atom has been substituted with a fluorine atom; Y and Z each represents, independently, an alkyl group of 1 to 10 carbon atoms in which at least one hydrogen atom has been substituted with a fluorine atom; R^1 to R^3 each represents, independently, an aryl group or an alkyl group, and at least one of R^1 to R^3 represents an aryl group]; and

an onium salt-based acid generator comprising a straight-chain fluorinated alkylsulfonate anion of 1 to 7 carbon atoms, wherein the blend ratio (weight ratio) between the onium salt-based acid generator and the one or more compounds selected from the sulfonium compounds is within a range from 1:9 to 9:1.

14. (Previously presented) A resist composition according to claim 13, wherein said structural units (a) comprise structural units (a1) derived from a (meth)acrylate ester comprising an acid dissociable, dissolution inhibiting group.

15. (Previously presented) A resist composition according to claim 14, wherein said structural units (a) further comprise structural units (a2) derived from a (meth)acrylate ester comprising a lactone-containing monocyclic or polycyclic group.

16. (Previously presented) A resist composition according to claim 14, wherein said structural units (a) further comprise structural units (a3) derived from a (meth)acrylate ester comprising a polar group-containing aliphatic hydrocarbon group.

17. (**Previously presented**) A resist composition according to claim 13, further comprising a nitrogen-containing organic compound.

18. (**Previously presented**) A method for forming a resist pattern, comprising the steps of forming a resist film on a substrate using a resist composition according to claim 13; conducting selective exposure treatment of said resist film; and alkali developing said resist film to form said resist pattern.

19. (**New**) A resist pattern formed using the method according to claim 12.

20. (**New**) A resist pattern formed using the method according to claim 18.